

INVITATION FOR QUOTATION

TEQIP-II/2014/CG1G02/Shopping/55

12-Dec-2014

To,

Sub: Invitation for Quotations for supply of Goods

Dear Sir,

1. You are invited to submit your most competitive quotation for the following goods with item wise detailed specifications given at Annexure I,

Sr. No	Brief Description	Quantity	Delivery Period(In days)	Place of Delivery	Installation Requirement (if any)
1	Firewall	1	60	Principal, Government Engineering College, Jagdalpur, Bastar, Dhrapura-3, Chhattishgarh-494005	Yes
2	L3 Managed Catalyst Switch	1	60	Principal, Government Engineering College, Jagdalpur, Bastar, Dhrapura-3, Chhattishgarh-494005	Yes
3	Wireless Access Point	40	60	Principal, Government Engineering College, Jagdalpur, Bastar, Dhrapura-3, Chhattishgarh-494005	Yes

4	Wireless USB Adoptor	40	60	Principal, Government Engineering College, Jagdalpur, Bastar, Dhramapura-3, Chhattishgarh-494005	Yes
---	----------------------	----	----	--	-----

2. Government of India has received a credit from the International Development Association (IDA) towards the cost of the **Technical Education Quality Improvement Programme[TEQIP]-Phase II** Project and intends to apply part of the proceeds of this credit to eligible payments under the contract for which this invitation for quotations is issued.
3. Quotation,
 - 3.1 The contract shall be for the full quantity as described above.
 - 3.2 Corrections, if any, shall be made by crossing out, initialing, dating and re writing.
 - 3.3 All duties and other levies payable by the supplier under the contract shall be included in the unit price.
 - 3.4 Applicable taxes shall be quoted separately for all items.
 - 3.5 The prices quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
 - 3.6 The Prices should be quoted in Indian Rupees only.
4. Each bidder shall submit only one quotation.
5. Quotation shall remain valid for a period not less than **55** days after the last date of quotation submission.
6. Evaluation of Quotations,

The Purchaser will evaluate and compare the quotations determined to be substantially responsive i.e. which

 - 6.1 are properly signed ; and
 - 6.2 confirm to the terms and conditions, and specifications.
7. The Quotations would be evaluated for all items together.
8. Award of contract:

The Purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price.

8.1 Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.

8.2 The bidder whose bid is accepted will be notified of the award of contract by the Purchaser prior to expiration of the quotation validity period. The terms of the accepted offer shall be incorporated in the purchase order.

9. Payment shall be made in Indian Rupees as follows:

Delivery and Installation - 100% of total cost

Satisfactory Acceptance - 0% of total cost

10. All supplied items are under warranty of **12** months from the date of successful acceptance of items.

11. You are requested to provide your offer latest by **16:00** hours on **03-Jan-2015** .

12. Detailed specifications of the items are at Annexure I.

13. Training Clause (if any) **No**

14. Testing/Installation Clause (if any) **Yes**

15. Information brochures/ Product catalogue, if any must be accompanied with the quotation clearly indicating the model quoted for.

16. Sealed quotation to be submitted/ delivered at the address mentioned below,
Government Engineering College, Jagdalpur, Dhramapura-3, Jagdalpur, Bastar

17. We look forward to receiving your quotation and thank you for your interest in this project.

(Authorized Signatory)

Name & Designation

Annexure I

Sr. No	Item Name	Specifications
1	Firewall	<p>Data Link Protocol: Gigabit Ethernet, Features: Firewall protection, VLAN support , VPN support, Form Factor: Rack-mountable, Network Transport Protocol: IPSec, Ports Qty: 8, Status Indicators: Active , Alarm , Boot state , HDD activity , Power , VPN, 1000Base-T, Compliant Standards: C-Tick , CISPR 22 , CSA C22.2 No. 60950-1-07, EMC , EN 60950-1 , EN 61000-3-2 , EN 61000-3-3 , EN55022 Class A , EN55024 , FCC Part 15 B Class A , ICES-003 , IEC 60950-1, KC , UL 60950-1, VCCI V-3, Encryption Algorithm: DES , Rack Mounting Kit: Included, Humidity Range Operating: 0 - 90%, Max Operating Temperature: 104 °F, Min Operating Temperature: 23 °F, Frequency Required: 50/60 Hz, Nominal Voltage: AC 120/230 V, Type: Internal power supply, Concurrent sessions Value: 500000, Virtual interfaces (VLANs) Value: 200, Firewall throughput Value: 2 Gbps, VPN throughput (3DES/AES) Value: 300 Mbps, Firewall + intrusion prevention throughput Value: 600 Mbps, RAM Installed Size: 12 GB, Users/nodes: Unlimited, IPsec VPN peers: 750, Cloud Web Security users: 4000, New connections per second: 20,000, Integrated I/O: 8 GE copper, Expansion I/O: 6 GE copper or 6 GE SFP, Dedicated management port: 1 GE, Serial ports: RJ-45 console, Minimum system flash: 8 GB, Steady state output: 75W, Maximum peak: 108W, AC current: 4.85A, DC domestic line voltage: - 40.5 to 56 VDC (-48 VDC nominal), DC current: 15A (maximum input).</p>
2	L3 Managed Catalyst Switch	<p>L3 managed switch, Fixed Uplinks: 4 x Gigabit Ethernet with Small Form-Factor Pluggable (SFP), Total 10/100/1000 Ethernet Ports:24, Default AC Power Supply: 250 WAC, Authentication Method: RADIUS , Secure Shell (SSH) , Compliant Standards: IEEE 802.1ab (LLDP) , IEEE 802.1D , IEEE 802.1p , IEEE 802.1Q , IEEE 802.1s , IEEE 802.1w , IEEE 802.1x , IEEE 802.3 , IEEE 802.3ab , IEEE 802.3ad (LACP) , IEEE 802.3u , IEEE 802.3x , IEEE 802.3z, Advanced Switching: Layer 3, Features:Access Control List (ACL) support , ARP support , DHCP snooping , Dynamic ARP Inspection (DAI) , Energy Efficient Ethernet , Flexible NetFlow (FNF) , IGMP snooping , IPv6 support , Link Aggregation Control Protocol (LACP) , MLD snooping , Multiple Spanning Tree Protocol (MSTP) support , Port Aggregation Protocol (PAgP) support , Quality of Service (QoS) , RADIUS support , Rapid Per-VLAN</p>

		Spanning Tree Plus (PVRST+) , Rapid Spanning Tree Protocol (RSTP) support , Remote Switch Port Analyzer (RSPAN) , Trunking , Uni-Directional Link Detection (UDLD) , Virtual Route Forwarding-Lite (VRF-Lite) , VLAN support, RAM Size: 4 GB, Features: StackWise-160, and takes advantage of the Unified Access Data Plane (UADP) application-specific integrated circuit (ASIC). This switch can enable uniform wired-wireless policy enforcement, application visibility, flexibility, application optimization, and superior resiliency. The Catalyst switch supports full IEEE 802.3at Power over Ethernet Plus (PoE+), and offers modular and field-replaceable redundant fans and power supplies. It can help you increase wireless productivity and reduce your TCO. Humidity Range Operating: 5 - 96% (non-condensing), Max Operating Temperature: 113 °F, Min Operating Temperature: 23 °F, Routing Protocol :BGP-4 , EIGRP for IPv6 , IS-IS , OSPFv3 , PIM-DM , PIM-SM , PIM-SSM , Policy-based routing (PBR) , RIP-1 , RIP-2 , RIPng , Static IP routing, Flash Memory: 2 GB.
3	Wireless Access Point	Standards: IEEE 802.11n, 802.11g, 802.11b, 802.3af, 802.3u, 802.1X (security authentication), 802.1Q (VLAN), 802.1D, (Spanning Tree), 802.11i (WPA2 security), 802.11e (wireless QoS), IPv4 (RFC 791), IPv6 (RFC 2460), Wireless Data Rates: Up to 450Mbps, Frequency Band: able radio band (2.4 or 5 GHz), Antenna: Internal Antenna of 5 dBi, System Requirements: 802.11b, 802.11g, 802.11n wireless adapter with TCP/IP protocol installed per PC Switch/router, Temperature: 0°C - 40°C (32°F - 104°F), Humidity: 10% - 85%, Non-Condensing, Gigabit Ethernet LAN interfaces with PoE, Maximum Active WLAN Clients: 64 per radio, MIMO Support: 3x3:3, Ethernet Port Speed:10/100/1000, Single Point Setup with clustering, Wi-Fi standards: a/b/g/n, Number of SSID Supported: 16.
4	Wireless USB Adopter	Standards: 802.11a, 802.11b, 802.11g, 802.11n, Bands: Simultaneous 2.4 GHz and 5 GHz, Transmit/Receive: 3 x 3 Antennas: 3 Internal, OS Compatibility: Windows, Windows XP SP3, Windows Vista SP1 or later, Windows 7 or Windows 8, Available USB 2.0 port, Adapter Base and USB Cap, Maximum speed (up to 450 Mbps) for fast wireless transfer rates, Dual-Band to help avoid interference and maximize throughput, Operates at either 2.4 or 5 GHz to avoid wireless interference, include with Adapter Cradle.

FORMAT FOR QUOTATION SUBMISSION

(In letterhead of the supplier with seal)

Date: _____

To:

Sl. No.	Description of goods (with full Specifications)	Qty.	Unit	Quoted Unit rate in Rs. (Including Ex Factory price, excise duty, packing and forwarding, transportation, insurance, other local costs incidental to delivery and warranty/ guaranty commitments)	Total Price (A)	Sales tax and other taxes payable	
						In %	In figures (B)
Total Cost							

Gross Total Cost (A+B): Rs. _____

We agree to supply the above goods in accordance with the technical specifications for a total contract price of Rs. ————— (Amount in figures) (Rupees —————amount in words) within the period specified in the Invitation for Quotations.

We confirm that the normal commercial warranty/ guarantee of ————— months shall apply to the offered items and we also confirm to agree with terms and conditions as mentioned in the Invitation Letter.

We hereby certify that we have taken steps to ensure that no person acting for us or on our behalf will engage in bribery.

Signature of Supplier

Name: _____

Address: _____

Contact No: _____